



Slip Check to AS 4586-2013 Seagrass Flamed and Brushed Marble

Report Number: R15141d Report Date: 7 November 2017 Total Number of Pages 2

NATA Accreditation Number 17139

Accredited for compliance with ISO/IEC 17025 - Testing

The results of the tests, calibrations and/or measurements included in this document are traceable to Australian/national standards

NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, medical testing, calibration and inspection reports

Issued by

Safe Environments Pty Ltd Unit 4, 40 Bessemer Street Blacktown NSW 2148 **Prepared for**

Artmar Tile and Stone 4-6 Smithfield Road Smithfield NSW 2164 Approved by

Dale Rowell
Authorised Signatory

Unit 4/40 Bessemer St Blacktown NSW 2148 Phone 02 9621 3706 info@SafeEnvironments.com.au



7 November 2017

Test Report No. R15141d

Slip Resistance Classification of New Pedestrian Surface Materials

AS 4586-2013 Appendix A (Wet Pendulum Test)

The slip resistance classification has been determined for unused surfaces using specific conditions. Factors such as usage, cleaning systems, applied coatings and patterns of wear may affect the characteristics of the surface after classification. Standards Australia Handbook 198:2014 *Guide to the specification and testing of slip resistance of pedestrian surfaces* provides guidance for the selection of slip resistant pedestrian surfaces classified in accordance with AS 4586-2013. It is recommended that this test report be read in conjunction with AS 4586 and HB 198.

Requested by: Artmar Tile and Stone Client Address: 4-6 Smithfield Road

Smithfield NSW 2164

Product Manufacturer: Supplied by Artmar Tile and Stone Product Description: Seagrass Flamed and Brushed Marble

Test conducted according to: AS 4586:2013 Appendix A

Location: 4/40 Bessemer Street, Blacktown NSW 2148

Conducted by: Ola Radzanowska

Date: 7 November 2017 Temperature: 23°C Sample: Unfixed Cleaning: None

Rubber slider used: Slider 96 Conditioned: Grade P 400 paper dry followed

Slope of specimen: Tested on a flat level surface by wet lapping film

Direction of Test: NA

	Specimen 1	Specimen 2	Specimen 3	Specimen 4	Specimen 5
Mean BPN of last 3 swings:	47	36	41	41	37

Reported SRV of Sample:	40	
Class:	Р3	